

AUTOMATIC VEHICLE THEFT PREVENTION SYSTEM

RELATED INVENTION

5 The present invention claims priority under 35 U.S.C. §119(e) to: "Automatic Vehicle Theft Prevention System," U.S. Provisional Patent Application Serial No. 60/196,343, filed 12 April 2000, which is incorporated by reference herein.

TECHNICAL FIELD OF THE INVENTION

10 The present invention relates to the field of vehicle theft prevention systems. More specifically, the present invention relates to a system that selectively enables the ignition system of a vehicle.

BACKGROUND OF THE INVENTION

15 In a conventional motor vehicle, the internal combustion engine of the vehicle is "started" by an ignition system that includes an electrical starter motor, a battery power source, and a key-operated ignition switch. When the ignition switch is closed, current is supplied by the battery power source to the starter motor, which in turn, "starts" the internal combustion engine.

20 Security of the ignition system is dependent upon the integrity of the key-operated ignition switch. By shorting the ignition switch, the ignition system circuitry can be closed without the need of a key to close the ignition switch. This is known as "hot wiring" starting. Shorting the ignition switch is frequently the method used to start the internal combustion engine during theft of a motor vehicle. The switch is typically located on the steering column of the vehicle which is surrounded by a circular metal housing. By breaking

25

30

open the metal housing, the switch may thereafter be quickly and easily shorted. Alternatively, the key switch may be broken by the forceful insertion of an object such as a screwdriver into the keyhole and the screwdriver thereafter effectively acts as a key to close the switch.

Several systems have been developed which attempt to make theft of the vehicle more difficult. Such systems include vehicle alarms that sound a siren or horn when a vehicle is broken into and/or prevent the vehicle from starting. Other systems are mechanical devices that secure to the steering column and/or the gas pedal to prevent their operation even when the car is hot wired. Unfortunately, audible alarms and mechanical devices require activation or installation by the driver. As such, they are often forgotten by the vehicle owner, and not enabled. In addition, audible alarms have become so commonplace that they are frequently ignored. Thus, these prior art audible alarms and mechanical devices are ineffective for satisfactorily protecting vehicles against theft.

Another system, known as a transponder-based immobilizer system, includes a contactless data carrier (transponder) embedded in the vehicle key. The transponder is powered by a radio frequency field generated by a radio frequency identification (RFID) reader in the vehicle. The transponder sends an authorization code to the RFID reader, which signals engine management electronics to immobilize the car if it does not find or does not accept the transmitted authorization code. The transponder-based immobilizer system is advantageous over prior art driver-activated alarms and mechanical devices because it requires no intervention by the driver in order to activate the immobilizer system.

While an immobilizer system can prevent theft of a vehicle by merely shorting the ignition key switch, such a system suffers from several disadvantages. For example, since the transponder is embedded on the key, the vehicle owner cannot readily have a duplicate key made. Rather, the vehicle owner is required to obtain duplicate keys through the vehicle dealer or through an authorized provider, which is inconvenient for the vehicle owner and significantly more expensive than merely having a duplicate key made at a local hardware store.

In addition, if the key with the embedded transponder is stolen, the thief can still start the car. Such situations arise in a home robbery where the thief finds the vehicle keys setting in the home or in a car jacking in which the thief takes the key from the driver.

Yet another problem arises with the prior art transponder-based immobilizer systems in that these systems are only provided in new vehicles by the original equipment manufacturer. As such, individuals having older model vehicles, collectable vehicles, a fleet of vehicles, and such, cannot employ this technology to protect their vehicles.

SUMMARY OF THE INVENTION

Accordingly, it is an advantage of the present invention that an automatic vehicle theft prevention system is provided that protects the vehicle against theft without the need for human intervention.

It is another advantage of the present invention to provide an automatic theft prevention system that selectively enables the ignition system of a vehicle.

It is another advantage of the present invention to provide an automatic vehicle theft prevention system that is separate from an ignition key of a vehicle.

Yet another advantage of the present invention is to provide an automatic vehicle theft prevention system as a cost effective, aftermarket device for protecting older vehicles from theft.

5 The above and other advantages of the present invention are carried out in one form by an automatic vehicle theft prevention system for selectively enabling an ignition system of a vehicle, the ignition system being operable using an ignition key. The system includes an interrogator circuit
10 having a signal generator for generating an excitation signal and an antenna coupled to the signal generator for radiating the excitation signal and receiving a return signal. A transponder circuit, separate from the ignition key, detects the excitation signal and radiates the return signal. The
15 transponder circuit modulates the excitation signal to produce the return signal containing an identification code for the transponder circuit. A controller is in communication with the antenna and detects the identification code in the return signal. A relay is actuated to an enable mode by the
20 controller when the controller detects the identification code, the relay being actuated to enable the ignition system.

BRIEF DESCRIPTION OF THE DRAWINGS

25 A more complete understanding of the present invention may be derived by referring to the detailed description and claims when considered in connection with the Figures, wherein like reference numbers refer to similar items throughout the Figures, and:

30 FIG. 1 shows a schematic view of a motor vehicle including an ignition system; and

 FIG. 2 shows a block diagram of an automatic vehicle theft prevention system interconnected with the ignition system of

the motor vehicle in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a schematic view of a motor vehicle 20 including an ignition system, generally referred to by an arrow 22. Motor vehicle 20 includes a passenger compartment 24 and an engine compartment 26 containing an engine 28. Ignition system 22 includes a battery power source 30, an ignition key switch 32, and a starter mechanism, or motor, 34 connected in series by wires 36, 38, and 40. Starter motor 34 includes a housing 42 and an armature 44 with a pinion 46 attached to the end of armature 44.

In general, when ignition key switch 32 of ignition system 22 is closed by the insertion and rotation of a key 48 in switch 32, a magnetic field is produced inside starter motor 34 which, in turn, causes armature 44 to be translated and rotated. Translation of armature 44 causes pinion 46 to contact a flywheel 50. Rotation of flywheel 50 is caused by rotation of armature 44, and in turn, causes engine 28 of motor vehicle 20 to "start".

FIG. 2 shows a block diagram of an automatic vehicle theft prevention system 52 interconnected with ignition system 22 of the motor vehicle 20 (FIG. 1) in accordance with a preferred embodiment of the present invention. System 52 is especially suited as an aftermarket device for cost effectively enhancing the integrity of the ignition systems of older model vehicles, collectable vehicles, and the like.

Theft prevention system 52 is interconnected in series between ignition key switch 32 and starter motor 34 along wire 38 of an existing motor vehicle, such as motor vehicle 20 (FIG. 1). In particular, system 52 includes an input 51 configured

to be coupled to an ignition switch output 53 of ignition switch 32. System 52 further includes an output 55 configured to be coupled to a starter motor input 57 of starter motor 34.

Generally, vehicle theft prevention system 52 includes an
5 interrogator circuit 54, in radio communication with a
transponder circuit 56. A controller 58, in communication with
interrogator circuit 54, is configured to selectively actuate
an enable relay 62. Enable relay 62, in turn, actuates a
latching relay 64. An override switch 60 is coupled to an
10 input of latching relay 64, which when activated, causes
latching relay 64 to remain in a latched state only following
actuation of latching relay 64 by enable relay 62.

Override switch 60, enable relay 62, and latching relay 64
are normally in an open position, as shown, to prevent
15 operation of motor vehicle 20. When each of override switch
60, enable relay 62, and latching relay 64 are in an open
position, an open circuit is created between ignition switch 32
and starter motor 34 along wire 38 so that ignition system 22
(FIG. 1) is disabled so that engine 26 (FIG. 1) cannot be
20 started. Vehicle theft prevention system 52 is configured to
enable ignition system 22 to start engine 26 (FIG. 1) without
the need for human intervention by selectively actuating enable
relay 62, which in turn, actuates latching relay 64, as
discussed below.

25 Interrogator circuit 54 includes a signal generator, or
coil, 66 for generating an excitation signal 68 and an antenna
70 for radiating excitation signal 68, as indicated by an arrow
72. Transponder circuit 56 detects and modulates excitation
signal 68 to produce a return signal 74 containing an
30 identification code 76 that identifies transponder circuit 56.
Return signal 74 is radiated from transponder circuit 56, as
indicated by an arrow 77.

Interrogator circuit 54 and transponder circuit 56 employ a radio frequency identification (RFID) technology. RFID is a technology that uses contactless communication to identify objects, to store data or values, or to secure information and access without physical or visual contact between interrogator circuit 54 and transponder circuit 56. Interrogator circuit 54 is commonly known as a data reader or a proximity reader.

In a preferred embodiment, excitation signal 68 is a continuous 125 kHz electromagnetic field radiated from signal generator 66. A coil (not shown) in transponder circuit 56 transmits identification code 76 using a 62.5 kHz electromagnetic field, one-half the value of excitation signal 68. The 62.5 kHz electromagnetic field, known as return signal 74, acts as an analog radio frequency carrier for identification code 76. Although the present invention employs a 125 kHz electromagnetic field, other frequencies commonly used for RFID and contactless data carrier may be employed. These other common frequencies include, for example, 2 to 15 MHz, 455 MHz, and 2.45 GHz.

Transponder circuit 56 is a mobile RFID data carrier that includes a memory element 78 containing identification code 76 and a transceiver, or coil (not shown) in a plastic housing unit or plastic card. Transponder circuit 56 may also include additional functions to secure, protect, or select access to transponder circuit 56, as known to those skilled in the art. Transponder circuit 56, including a transponder/receiver pair and memory element 78, is variously referred to as a tag, card, transponder, electronic label, code plate, and so forth.

Transponder circuit 56 contains no internal power source. Rather, transponder circuit 56 is externally powered and derives its power from the excitation signal 68, radiated from interrogator circuit 54. Since power is provided to

transponder circuit 56 by excitation signal 68, there is no need for batteries inside transponder circuit. Thus, cost savings is achieved through the simplicity of design of transponder circuit 56 and because there is no need for battery replacement.

Transponder circuit 56 is separate from key 48 (FIG. 1). Consequently, the high cost to have special keys fabricated that include an embedded transponder circuit for use with their older model vehicles need not be incurred by the vehicle owner. Moreover, transponder circuit 56 is ideally kept disconnected from a key ring (not shown) to which key 48 is connected. Thus, transponder circuit 56 may be stored in a wallet, handbag, and so forth so that a thief having access to key 48, but not having access to transponder circuit 56, cannot start engine 26 (FIG. 1) of motor vehicle 20. For example, in the case of an attempted carjacking, the driver can merely shut off vehicle 20, leave key 48 in the ignition, and run away from vehicle 20 taking transponder circuit 56 with them in their wallet or purse. By the time a thief discontinues attempting to start vehicle 20, the driver will be safely away from vehicle 20. When the driver later returns, vehicle 20 might likely still be where the thief left it.

Controller 58 and signal generator 66 of interrogator 54 may be housed in a common housing within passenger compartment 24 (FIG. 1) or within engine compartment 26 (FIG.1). However, since system 52 relies on proximity sensing, antenna 70 is configured for placement inside passenger compartment 24 (FIG. 1) of motor vehicle 20 (FIG. 1) preferably close to the driver side seat. For example, antenna 70 may be embedded inside the driver side seat cushion or beneath the seat cushion so that antenna 70 and transponder 56 are likely to be in close

proximity, for example, within twenty inches, in order for interrogator circuit 70 to detect return signal 74.

A radio frequency (RF) receiver (not shown) of controller 58 is in communication with antenna 70 of interrogator circuit 54. In addition, controller 58 is in communication with an output of ignition key switch 32 via an ignition link 80 for detecting a closure and opening of ignition switch 32.

Controller 58 may be powered via ignition link 80 from battery source 30 whenever ignition switch is closed. Alternatively, controller 58 may include nonvolatile memory, or separate batteries, so that controller 58 does not depend upon battery power source 30 and the closure of ignition key switch 32 for power.

As mentioned briefly above, controller 58 is configured to actuate enable relay 62. Thus, controller 58 is in communication with a coil of enable relay 62 via an enable link 84. In addition, an output 85 of enable relay 62 is in communication with a coil of latching relay 64 via a latching link 86. An output 88 of override switch 60 is also in communication with an input to latching relay 64 via a bypass link 90. Output 88 of override switch 60 further couples with an indicator 92 via an indicator link 94.

Override switch 60 may be a panel mounted button, toggle switch, and the like located inside passenger compartment 24 (FIG. 1) of motor vehicle 22 (FIG. 1). An input of override switch 60 is coupled to a low power source 93 which supplies power to bypass link 90 and indicator link 94 when override switch 60 is activated. Indicator 92 may be a lamp, a light emitting diode, a liquid crystal display, a speaker circuit, and the like located inside passenger compartment 24 that is energized when override switch 60 is activated, or closed (discussed below).

Controller 58 includes an input for receiving a predetermined authorized identification code 96 from an external programming device 98, shown in ghost form. A memory element 100 of controller 58 is in communication with the input for storing predetermined authorized identification code 96. In one embodiment, the input is a data port 102 configured for a wired interconnection 104 with programming device 98. In another embodiment, programming device 98 is a wireless transmitter, and the input is antenna 70 configured for radio frequency communication with programming device 98 over a wireless communication link 106.

Predetermined authorized identification code 96 corresponds to identification code 76. That is, when automatic vehicle theft prevention system 52 is installed into motor vehicle 20 (FIG. 1), controller 58 is programmed, using programming device 98, to recognize identification code 76 for transponder circuit 56. When controller 58 recognizes identification code 76 in return signal 74, controller 58 actuates system 52 in an enable mode (discussed below) to enable ignition system 22 (discussed below).

System 52 may be actuated to the enable mode by more than one transponder circuit so that more than one user is authorized to use motor vehicle 20 (FIG. 1). Such a scenario occurs when there are multiple drivers in a household, when vehicle 20 is one of a fleet of company owned vehicles that may be driven by a number of individuals, and so forth. In particular, the input of controller 58, either data port 102 or antenna 70, is configured to receive a number of predetermined authorized identification codes 96. Likewise, memory element 100 of controller 58 is configured to store the additional predetermined authorized identification codes.

By way of example, transponder circuit 56 is a first RFID data carrier and system 52 includes a second RFID data carrier transponder circuit 108, separate from key 48 (FIG. 1) and similar in function to transponder circuit 56. Second RFID data carrier 108, has a memory element 110 for storing a second identification code 112. A second predetermined authorized identification code 114, corresponding to second identification code 112, is received at the input of controller 58 and stored in memory element 100. With both of predetermined authorized identification codes 96 and 114 stored in memory element 98 of controller 58, when controller 58 detects either of identification codes 76 or 112, controller 58 actuates system 52 in the enable mode (discussed below) to enable ignition system 22 (discussed below).

In a preferred embodiment, controller 58 is programmed with predetermined authorized identification codes corresponding to particular transponder circuits 56. However, in an alternative embodiment, other RFID systems may be employed in which the transponder circuit is programmed with particular identification code, or both the transponder circuits and the controller are programmed with corresponding identification codes.

In operation, following installation of system 52 in series with ignition system 22 (FIG. 1) and following the programming of controller 58 with authorized identification codes 96 and 114, system 52 is set to a disable mode. That is, override switch 60, enable relay 62, and latching relay 64 are set to open positions, which effectively opens ignition system 22 circuitry so that ignition system 22 cannot be enabled and engine 28 (FIG. 1) cannot be started.

System 52 is maintained in this disable mode whenever controller 58 fails to detect either of identification codes 76

and 112. Thus, a thief is deterred from stealing motor vehicle 20 (FIG. 1) by hot wiring or forcing ignition switch 32, or even by using key 48. Another advantage of the present invention, is that when a driver stores transponder circuit 56
5 separate from key 48, for example, in his or her wallet or purse, a driver cannot inadvertently drive away without their wallet or purse because the ignition system cannot be enabled without first detecting one of identification codes 76 and 112 stored in transponder circuits 56 or 108.

10 Interrogator 54 substantially continuously generates and radiates excitation signal 68. Thus, in order to operate motor vehicle 20, the driver merely enters vehicle 20 carrying one of transponder circuits 56 and 108. System 52 is placed in an enable mode following an access decision by controller 58.
15 More particularly, when a transponder circuit, for example transponder circuit 56, is moved close to antenna 70 such that antenna 70 receives return signal 74, interrogator circuit 54 passes return signal 74 on to the RF receiver of controller 58 for decoding. Controller 58 processes, error checks, and
20 converts return signal 74 to a digital signal.

Controller 58 then attempts to match identification code 76 within the digitized return signal 74 with one of predetermined authorized identification codes 96 and 114 in memory element 100. When controller 58 detects a match, controller actuates
25 enable relay 62. Enable relay 62 is a momentary relay indicating that an authorized transponder circuit 56 is present. Thus, enable relay 62 is actuated to a momentary closed state whenever a match is detected.

In response to the momentary actuation of enable relay 62,
30 latching relay 64 is also actuated to a latched, or closed, state. Thus, latching relay is closed in response to a detected match by controller 58 which causes momentary closure

of enable relay 62. As a convenience to the driver, latching relay 64 is adapted to remain latched even when motor vehicle 20 stalls, so that transponder circuit 56 need not be re-presented to interrogator 54. Latching relay 64 is reset
5 whenever ignition switch 32 is turned off or deactivated, as detected via ignition link 80 by controller 58.

Accordingly, in response to the momentary closure of enable relay 62 and sustained closure of latching relay 64, a circuit path is formed from ignition switch output 53 through input 51
10 and latching relay 64 to output 55 and to input 57 of starter motor 34. This circuit path allows system 52 to be in the enable mode so that when key 48 (FIG. 1) is inserted in ignition switch 32 and turned, engine 28 (FIG. 1) of motor vehicle may be started. Whenever switch 32 is turned off using
15 key 48, latching relay 64 opens and automatic vehicle theft prevention system 52 is placed back into the disable mode.

On occasion, it may be desirable to override system 52 such that ignition switch 32 is continuously enabled. Such a situation may arise, for example, when motor vehicle 20 (FIG.
20 1) is being turned over to an attendant for valet parking, when motor vehicle is in an automotive shop or at a carwash, and so forth. When a driver wishes to override system 52, the driver again enters vehicle 20 carrying one of transponder circuits 56 and 108. Again, controller 58 automatically attempts to match
25 a detected identification signal, such as identification code 76, with one of predetermined authorized identification codes 96 and 114 in memory element 100. When controller 58 detects a match, controller 58 again automatically actuates enable relay 62, which in turn actuates latching relay 64.

30 However, since the driver wishes to override system 52, it is incumbent upon the driver to activate override switch 60 which causes latching relay 64 to remain latched, or closed,

following actuation of latching relay 64 by enable relay 62. In addition, activation of override switch 60 energizes indicator 92 to provide visual or audible indication to the driver that override switch 60 is activated. Override switch
5 60 is subsequently deactivated so that system 52 is no longer bypassed by the driver deactivation, or switching off, override switch 60.

Accordingly, in response to the momentary closure of enable relay 62, causing latching relay 64 to be latched to a closed
10 position, and sustained closure of override switch 60, even when vehicle 20 is turned off, a circuit path is formed from ignition switch output 53 through input 51 and latching relay 64 to output 55 and to input 57 of starter motor 34. This circuit path allows system 52 to be bypassed or overridden so
15 that whenever key 48 (FIG. 1) is inserted in ignition switch 32 and turned, engine 28 (FIG. 1) of motor vehicle may be started, without first detecting return signal 74 having an identification code 76 that matches one of predetermined authorized identification codes 96 and 114. Thus, transponder
20 circuit 56 need not be turned over to an unauthorized individual such as a garage attendant or mechanic.

In summary, the present invention teaches of an automatic vehicle theft prevention system that protects a vehicle against theft without the need for human intervention. In particular,
25 the vehicle theft prevention system employs proximity sensing using an interrogator circuit and transponder circuit system to selectively enable relays interconnected between an ignition switch and a starter motor of an ignition system the vehicle. The transponder circuit is separate from the ignition key of a
30 vehicle so if a thief obtains a key for the vehicle, the thief will be prevented from readily starting the vehicle. The automatic vehicle theft prevention system is readily installed

and is a cost effective, aftermarket device for protecting older vehicles from theft.

5 Although the preferred embodiments of the invention have been illustrated and described in detail, it will be readily apparent to those skilled in the art that various modifications may be made therein without departing from the spirit of the invention or from the scope of the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217